EAGLE EYE
POWER SOLUTIONS

Flooded Battery

5 OPzS350 (2V350AH)

Specification

Nominal Voltage	2V	
Capacity(10HR)	350.0AH (1.8V/cell,20°C)	
Dimension	Length	124±2mm (4.88 inches)
	Width	206±3mm (8.11 inches)
	Container Height	471±3mm (18.54 inches)
	Total Height (with Terminal)	526±3mm (20.71 inches)
Approx Weight	Without Electrolyte 21.3 kg (46.86lbs)	
	With Electrolyte 28.3 kg (62.3lbs)	
Container Material	SAN transparent container	
Rated Capacity	350.0 AH/35.0A	(10hr,1.80V/cell,25°C/77°F)
	311.0 AH/62.2A	(5hr,1.75V/cell,25°C/77°F)
	270.0 AH/90.0A	(3hr,1.75V/cell,25°C/77°F)
	199.9 AH/199.9A	(1hr,1.60V/cell,25°C/77°F)
Max. Discharge Current	2800A (5s)	
Internal Resistance	Approx 0.65mÙ	
Operating Temp.Range	Discharge : -15～50°C (5～122°F)	
	Charge : 0～40°C (32～104°F)	
	Storage : -15～40°C (5～104°F)	
Type and number of poles	M8/2	
Charging	Floating voltage: 2.23V~2.25V at 20°C(68°F)Temp.	
	Boost charge: 2.30V~2.40V at 20°C(68°F)Temp.	
	Charging current(max.): 0.1CA	
	Temp.Coefficient -3mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge (4% per month)	Leoch OPzS batteries may be stored for up to 6 months at 20°C(68°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	

Applications

- *Telecommunications.*
- *Radio and cellular telephone relay stations.*
- *Emergency lighting systems.*
- *Power stations, Conventional power stations,*
- *Alternative power (solar, wind).*
- *Large UPS and computer back-up.*
- *Railway signalling.*
- *Maritime standby power on ships and ashore.*
- *Standby power.*
- *Buoy lighting.*
- *Long service life, designed life 15-20 years.*

Constant Current Discharge (Amperes) at 20 °C (68°F)

F.V/Time	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V/cell	265.3	230.5	199.9	157.5	130.2	97.3	78.2	66.2	57.3	45.3	37.4	20.3
1.65V/cell	249.2	221.7	193.2	153.5	127.2	95.7	77.1	65.3	56.5	44.8	37.0	20.1
1.70V/cell	236.6	209.1	185.9	148.6	124.3	92.9	75.3	63.9	55.4	44.0	36.4	19.8
1.75V/cell	221.9	199.3	176.4	141.6	119.0	90.0	73.1	62.2	54.1	43.2	35.8	19.5
1.80V/cell	197.4	179.7	162.4	132.8	111.8	85.4	69.9	59.6	52.1	42.1	35.0	19.1
1.85V/cell	157.5	148.9	139.0	118.1	101.5	78.2	64.7	55.9	49.1	40.0	33.5	18.4

Constant Power Discharge (Watts) at 20 °C (68°F)

F.V/Time	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V/cell	452.9	403.4	354.8	283.1	236.8	178.2	144.5	123.1	107.2	85.2	70.7	38.5
1.65V/cell	434.6	392.5	345.9	277.4	232.5	176.1	143.1	122.0	106.3	84.6	70.2	38.3
1.70V/cell	418.3	374.1	335.2	270.3	228.1	171.8	140.4	119.9	104.6	83.4	69.3	37.9
1.75V/cell	398.9	360.3	321.2	259.5	220.0	167.4	136.8	117.2	102.4	82.3	68.4	37.4
1.80V/cell	359.7	329.9	299.5	246.0	208.6	160.2	131.8	112.9	99.3	80.5	67.3	36.9
1.85V/cell	291.8	277.3	260.0	221.8	191.4	148.2	123.2	106.8	94.2	77.1	65.0	35.8

Specifications subject to change without notice.

Dimensions

Terminal (mm)







Discharge Characteristics



Charge voltage Vs ambient temperature curve



Discharge capacity Vs Ambient temperature curve (I10A)



Relantion curves of service life and ambient temperature



Self Discharge Characteristics



A No supplementary charge required
(Carry out supplementary charge before use if 100% capacity is required.)

B Supplementary charge required before use.Optional charging way as below:
1.Charged for above 3 days at limted current 0.1CA and constant volatge 2.25V/cell.
2.Charged for above 20hours at limted current 0.1CA and constant volatge 2.45V/cell.
3.Charged for 8~10hours at limted current 0.05CA .

C Supplementary charge may often fail to recover the capacity.
The battery should never be left standing till this is reached.

Eagle Eye Power Solutions, LLC
4031 W Kiehnau Ave.
Milwaukee, WI, 53209

Sales & Support
1-877-805-3377
info@eepowersolutions.com

www.eepowersolutions.com