EAGLE EYE
POWER SOLUTIONS

OPzV Series-Tubular Gel


12V 10OPzV200(12V200Ah)

Specifications

Rated Voltage		12V
Nominal Capacity	200.0Ah	(C_{10},1.80V/cell)
Dimension	Length Width Container Height Total Height	522mm(20.55 in.) 268mm(14.49 in.) 220mm(8.66 in.) 226mm(8.90 in.)
Approx Weight		75.9Kg (167.33 lbs)
Terminal		M8
Container Material		ABS
Rated Capacity (25°C)	200.0 Ah 175.5 Ah 155.7 Ah 112.0 Ah	(10hr,20.0A,1.80V/cell) (5hr,35.1A,1.75V/cell) (3hr,51.9A,1.75V/cell) (1hr,112.0A,1.67V/cell)
Max. Discharge Current(5s)		1600A
Internal Resistance(25℃)		Approx.4.8mΩ
Operating Temp.Range	Discharge Charge Storage	-20°C~55°C (-4°F~131°F) 0°C~40°C (32°F~104°F) -20°C~50°C (-4°F~122°F)
Nominal Operating Temp. Range		25±3°C (77±5°F)
Max.Charging Current(25°C)		50.0A
Charge voltage(25°C)	Float Temp. Coefficient Cycle(Equalization)	13.5V -3mV/cell/°C 14.1~14.4V
Effect of temp. to Capacity	40°C (104°F) 25°C (77°F) 0°C (32°F)	106% 100% 86%
Self Discharge		≤3% per month at 25°C



Layout



Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	10min	15min	30min	1h	2h	3h	5h	8h	10h
1.85V/cell	171.0	155.0	122.0	89.7	60.8	46.7	31.9	22.2	18.7
1.80V/cell	210.0	188.0	142.0	101.0	66.8	50.8	34.4	23.8	20.0
1.75V/cell	248.0	210.0	152.0	105.0	68.6	51.9	35.1	24.2	20.3
1.70V/cell	279.0	230.0	161.0	109.0	70.4	53.0	35.6	24.5	20.5
1.67V/cell	299.0	242.0	167.0	112.0	71.9	54.0	36.2	24.8	20.8
1.60V/cell	313.0	251.0	171.0	114.0	72.8	54.6	36.5	25.0	20.9

Constant Power Discharge (Watts/cell) at 25 °C (77°F)

F.V/Time	10min	15min	30min	1h	2h	3h	5h	8h	10h
1.85V/cell	318.0	292.0	233.0	174.0	118.0	91.2	62.7	44.1	37.3
1.80V/cell	384.0	348.0	269.0	194.0	129.0	98.8	67.4	47.1	39.7
1.75V/cell	446.0	384.0	284.0	201.0	132.0	101.0	68.5	47.8	40.3
1.70V/cell	492.0	413.0	298.0	207.0	135.0	102.0	69.3	48.3	40.7
1.67V/cell	519.0	430.0	307.0	212.0	137.0	104.0	70.1	48.7	41.0
1.60V/cell	532.0	439.0	311.0	214.0	138.0	104.0	70.6	49.0	41.3

EAGLE EYE
POWER SOLUTIONS

OPzV Series-Tubular Gel

12V 10OPzV200(12V200Ah)

Applications

- Telecommunications
- Radio and cellular telephone relay stations
- Emergency lighting systems
- Power stations,Conventional power stations, alternative pwer(solar,wind)
- Large UPS and computer back-up
- Railway signaling
- Maritime standby power on ships and ashore
- Process and control engineering
- Standby power
- Buoy lighting


General Features

- 20 years design life(20℃)
- Better recovery performance
- Wide working temperature range (-20~55)℃
- No electrolyte stratification provides longer service life
- High recombination efficient
- Build in copper core based in lead will carry large current
- Separator imported form AMER-SIL high porosity. PVC-$SiO_2$and low resistance
- Pasted negative plate special grid design increase the active material.availablity large current discharge and charge ability
- Tubuler type positive plate (polyester tube) prevent the active material from falling. Muti metal alloy pressed positive grid increase the anti corrosion ablity and service life


Standards

- Compliance with IEC 60896, IEC 61427, DIN 40742 standards
- CE, IEC Certified
- Manufactured in Leoch®IATF16949, ISO 45001,ISO 9001 and ISO 14001 certified production facilities


Charge voltage vs ambient temperature curve




Temperature effects in relation to battery capacity



Cycle Life in Relation to DOD



General Relation of Capacity VS. Storage Time



Eagle Eye Power Solutions, LLC
4031 W Kiehnau Ave.
Milwaukee, WI, 53209

Sales & Support
1-414-962-3377
info@eepowersolutions.com

www.eepowersolutions.com