EAGLE EYE
POWER SOLUTIONS

OPzV Series-Tubular Gel

24 OPzV3000(2V3000Ah)

Specifications

Rated Voltage		2V
Nominal Capacity	3000Ah	(C_{10},1.80V/cell)
Dimension	Length Width Container Height Total Height	576mm(22.68 in.) 212mm(8.34 in.) 772mm(30.39 in.) 807mm(31.77 in.)
Approx Weight		232.0Kg (511.47 lbs)
Terminal		M8
Container Material		ABS
Rated Capacity (25°C)	3000.0 Ah 2616.5Ah 2322.6 Ah 1673.8 Ah	(10hr,300.0A,1.80V/cell) (5hr,523.3A,1.75V/cell) (3hr,774.2A,1.75V/cell) (1hr,1673.8A,1.67V/cell)
Max. Discharge Current(5s)		24000A
Internal Resistance(25℃)		Approx.0.23mΩ
Operating Temp.Range	Discharge Charge Storage	-20°C~55°C (-4°F~131°F) 0°C~40°C (32°F~104°F) -20°C~50°C (-4°F~122°F)
Nominal Operating Temp. Range		25±3°C (77±5°F)
Max.Charging Current(25°C)		750.0A
Charge voltage(25°C)	Float Temp. Coefficient Cycle(Equalization)	2.25V -3mV/cell/°C 2.35~2.40V
Effect of temp. to Capacity	40°C (104°F) 25°C (77°F) 0°C (32°F)	106% 100% 86%
Self Discharge		≤3% per month at 25°C

Layout



Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	10min	15min	30min	1h	2h	3h	5h	8h	10h
1.85V/cell	1751.0	1708.0	1562.0	1340.7	906.7	696.0	476.1	333.7	281.1
1.80V/cell	2154.0	2068.0	1820.0	1503.0	993.0	757.0	513.0	357.0	300.0
1.75V/cell	2548.0	2314.0	1940.0	1562.8	1027.5	774.2	523.3	363.0	305.1
1.70V/cell	2859.0	2526.0	2054.0	1631.1	1053.4	789.7	531.0	368.2	308.6
1.67V/cell	3071.0	2667.0	2136.0	1673.8	1070.7	804.3	539.6	372.5	311.1
1.60V/cell	3212.0	2762.0	2191.0	1699.4	1088.0	813.7	544.7	375.1	313.7

Constant Power Discharge (Watts/cell) at 25 °C (77°F)

F.V/Time	10min	15min	30min	1h	2h	3h	5h	8h	10h
1.85V/cell	3257.0	3210.0	2985.0	2587.6	1761.5	1357.6	935.1	661.4	558.9
1.80V/cell	3936.0	3831.0	3444.0	2895.0	1925.6	1469.3	1003.7	707.1	595.7
1.75V/cell	4576.0	4228.0	3634.0	2988.9	1968.7	1495.1	1020.9	717.4	604.3
1.70V/cell	5045.0	4548.0	3807.0	3091.4	2011.9	1520.9	1038.0	725.2	610.3
1.67V/cell	5320.0	4731.0	3920.0	3151.2	2046.4	1546.7	1046.6	732.1	615.4
1.60V/cell	5460.0	4828.0	3979.0	3185.3	2063.7	1555.2	1055.2	735.6	618.9

EAGLE EYE
POWER SOLUTIONS

OPzV Series-Tubular Gel

24 OPzV3000(2V3000Ah)

Applications

- Telecommunications
- Radio and cellular telephone relay stations
- Emergency lighting systems
- Power stations,Conventional power stations, alternative pwer(solar,wind)
- Large UPS and computer back-up
- Railway signaling
- Maritime standby power on ships and ashore
- Process and control engineering
- Standby power
- Buoy lighting

General Features

- 20 years design life(20℃)
- Better recovery performance
- Wide working temperature range (-20~55)℃
- No electrolyte stratification provides longer service life
- High recombination efficient
- Build in copper core based in lead will carry large current
- Separator imported form AMER-SIL high porosity. PVC-$SiO_2$and low resistance
- Pasted negative plate special grid design increase the active material.availablity large current discharge and charge ability
- Tubuler type positive plate (polyester tube) prevent the active material from falling. Muti metal alloy pressed positive grid increase the anti corrosion ablity and service life

Standards

- Compliance with IEC 60896, IEC 61427, DIN 40742 standards
- UL, CE Certified
- Manufactured in Leoch®IATF16949, OHSAS 18001,ISO 9001 and ISO 14001certified production facilities

Charge voltage vs ambient temperature curve



Temperature effects in relation to battery capacity



Cycle Life in Relation to DOD



General Relation of Capacity VS. Storage Time



Eagle Eye Power Solutions, LLC
4031 W Kiehnau Ave.
Milwaukee, WI, 53209

Sales & Support
1-414-962-3377
info@eepowersolutions.com

www.eepowersolutions.com