

BC-2500™

Industrial Battery Charger



Discover what makes the BC-2500 a game changer - tailored to meet the specific requirements of the smart grid:

- 1 Unmatched innovative and intuitive technology
- 2 Lightweight design with multiple modules in a single chassis
- 3 TPL-001-5 compliant with fully redundant architecture and continuity testing capabilities

Hot Swappable Intelligent Power Modules (iPMs)

Natural Convection Cooled (No Fans)

AC/DC Powered UIM for continued operation without AC

Heavy-duty Construction for ruggedness and reliability



Low Ripple – battery eliminator option standard

Universal AC input: 100-240 Vac, 50-200 Hz

Battery Temperature Compensation with controlled limits

High Energy Efficiency of > 93% at 240 Vac and > 91% at 120 Vac and full load



WEB-BASED SOFTWARE INFORMATION

Access on any PC, laptop or mobile device to view measure parameters in real-time

Log up to 10,000 history records, downloadable to a CSV file

Ethernet communication standard for field or remote monitoring

APPLICATIONS

- Utility
- Switchgear
- Process Control
- Other Industrial Applications

BC-2500 KIT

- 30 ft. remote temperature sense cable
- 30 ft. remote voltage sense cable
- High interrupt breakers
- Mounting rack



Book a demo today!

