



VRLA AGM Lead Acid

Product Overview

Eagle Eye offers full lines of AGM (Absorbed Glass Mat) batteries to cover a wide range of industries and uses. Sealed VRLA batteries are non-spillable which lends them to uses in deep-cycling, deep-discharge, standby, emergency backup, and other applications. AGM batteries are proven to perform in extreme conditions including great performance in cold environments.

Benefits

- Flexibility in terminal positions to suite the application needs (front and top mount options)
- Non spillable
- Low self-discharge rates for long shelf life
- None to minimal gassing
- Easy to transport (non-hazmat)
- Low maintenance design
- Does not need electrolyte replenished

Applications

- UPS
- Emergency lighting
- Renewables, solar and wind
- Telecommunications and switching
- Marine
- Engine starting
- Standby backup power

VRLA AGM Lead Acid Battery Models (Small Size)

Model	Rated voltage	20 Hr	10 Hr	Length		Width		Height		TH		Weight		Terminal Type
	V	1.75/cell	1.75/cell	mm.	in.	mm.	in.	mm.	in.	mm.	in.	kg	lbs.	
EE-LPL6-6.5	6	6.5	6.46	150	5.91	34	1.3	94	3.7	100	3.9	1.3	2.8	T2
EE-LPL6-9.0	6	9.0	8.95	151	5.94	51	2.0	94	3.7	100	3.9	1.7	3.7	T2
EE-LPL6-11	6	11.0	10.9	151	5.94	51	2.0	94	3.7	100	3.9	2.0	4.3	T2
EE-LPL6-18	6	18.0	17.9	157	6.18	83	3.3	125	4.9	125	4.9	3.2	7.1	T3-A
EE-LPL12-4.5	12	4.5	4.47	151	5.94	53	2.1	93	3.7	99	3.9	1.9	4.2	T1
EE-LPL12-7.0	12	7.0	6.92	151	5.94	65	2.6	93.5	3.7	99.5	3.9	2.5	5.4	T2
EE-LPL12-12	12	12.0	11.6	151	5.94	98	3.9	95	3.7	101	4.0	3.9	8.5	T2
EE-LPL12-18	12	18.0	17.0	181.5	7.15	77	3.0	167.5	6.6	167.5	6.6	5.7	12.6	T3
EE-LPL12-24	12	25.4	23.8	166.0	6.54	175	6.9	125	4.9	125	4.9	7.8	17.2	T12 (M5)
EE-LPL12-28H	12	28.0	26.3	164	6.46	125	4.9	176	6.9	176	6.9	9.1	20.1	T3-A
EE-LPL12-28	12	28.0	26.3	166.0	6.54	175	6.9	125	4.9	125	4.9	8.6	19.0	T3

BATTERIES

VRLA AGM Lead Acid

VRLA AGM Lead Acid Battery Models (Middle Size and 2V Series)

Model	Rated voltage	20 Hr	10 Hr	Length		Width		Height		TH		Weight		Terminal Type
	V	1.8/cell	1.8/cell	mm.	in.	mm.	in.	mm.	in.	mm.	in.	kg	lbs.	
EE-LPL12-38	12	40.6	38.0	197	7.76	165	6.5	170	6.7	170	6.7	13.2	29.1	T6
EE-LPL12-45	12	45.0	42.0	197	7.76	165	6.5	170	6.7	170	6.7	14.5	32.0	T6
EE-LPL12-55	12	59.0	55.0	229	9.02	138	5.4	210	8.3	230	9.1	17.7	39.0	T9
EE-LPL12-60	12	63.6	60.0	260	10.24	168	6.6	210	8.3	216	8.5	20.7	44.1	T6 (M6)
EE-LPL12-65	12	68.2	65.0	348	13.70	167	6.6	178	7.0	178	7.0	21.2	46.7	T6 (M6)
EE-LPL12-70	12	75.0	70.0	348	13.70	167	6.6	178	7.0	178	7.0	24.0	52.9	T6 (M6)
EE-LPL12-75	12	80.2	75.0	260	10.24	168	6.6	208	8.2	214	8.4	22.7	50.1	T6 (M6)
EE-LPL12-90H	12	95.4	90.0	306	12.05	168	6.6	208	8.2	230	9.1	27.1	59.8	T14
EE-LPL12-100	12	107.0	100	330	12.99	173	6.8	212	8.3	220	8.7	32.0	70.6	T11 (M8)
EE-LPL12-120	12	128.4	120	408	16.06	177	7.0	225	8.9	225	8.9	36.6	80.7	T11 (M8)
EE-LPL12-140	12	149.8	140	345	13.58	172	6.8	274	10.8	280	11.0	45.5	100.3	T11 (M8)
EE-LPL12-150	12	160.5	150	483	19.02	170	6.7	238.5	9.4	238.5	9.4	47.2	104.1	T11 (M8)
EE-LPL12-200	12	214.0	200	522	20.55	240	9.4	218	8.6	224	8.8	64.0	141.1	T11 (M8)
EE-LPL12-250	12	268.0	250	522	20.55	268	10.6	220	8.7	226	8.9	74.0	163.2	T11 (M8)
EE-LPL6-180	6	190.8	180	306	12.05	168	6.61	222	8.7	228	9.0	30.3	66.8	M6
EE-LPL2-100	2	106.8	100	170	6.69	72	2.8	205	8.1	214	8.3	5.8	13.0	T6 (M6)
EE-LPL2-150	2	160.0	150	170	6.69	98	3.9	205	8.1	214	8.3	8.4	18.7	T7
EE-LPL2-200	2	214.0	200	170	6.69	110	4.3	328	12.9	350	13.8	13.5	29.8	T11 (M8)
EE-LPL2-250	2	266.0	250	170	6.69	110	4.3	328	12.9	350	13.8	14.3	31.5	T11 (M8)
EE-LPL2-300	2	320.0	300	170	6.69	150	5.9	330	13.0	350	13.8	18.8	41.4	T11 (M8)
EE-LPL2-400	2	426.0	400	210	8.27	175	6.9	330	13.0	350	13.8	25.5	56.2	T11 (M8)
EE-LPL2-450	2	480.0	450	210	8.27	175	6.9	330	13.0	350	13.8	26.0	57.3	T11 (M8)
EE-LPL2-500	2	534.0	500	240	9.45	175	6.9	328	12.9	348	13.7	30.0	66.1	T11 (M8)
EE-LPL2-600	2	640.0	600	300	11.8	175	6.9	330	13.0	350	13.8	37.0	81.6	T11 (M8)
EE-LPL2-800	2	854.0	800	410	16.1	175	6.9	330	13.0	350	13.8	50.4	111.1	T11 (M8)
EE-LPL2-1000	2	1068.0	1000	475	18.7	175	6.9	328	12.9	350	13.8	60.0	132.3	T11 (M8)
EE-LPL2-1200	2	1280.0	1200	475	18.70	175	6.9	328	12.9	350	13.8	67.1	147.9	T11 (M8)
EE-LPL2-1500	2	1600.0	1500	403	15.87	354	13.9	339	13.3	349	13.7	97.8	215.6	T11 (M8)
EE-LPL2-2000	2	2134.0	2000	490	19.29	350	13.8	339	13.3	349	13.7	121.0	266.8	T11 (M8)
EE-LPL2-3000	2	3202.0	3000	709	27.9	350	13.8	337	13.3	347	13.7	183.0	403.4	T11 (M8)
EE-LPL2-200M	2	212	200	90	3.5	181	7.13	350	13.78	365	14.37	12.4	27.3	T11(M8)
EE-LPL2-300M	2	318	300	124	4.9	181	7.13	350	13.78	365	14.37	18.0	39.7	T11(M8)
EE-LPL2-400M	2	424	400	158	6.2	181	7.13	350	13.78	365	14.37	22.7	50.0	T11(M8)
EE-LPL2-500M	2	530	500	191	7.5	181	7.13	350	13.78	365	14.37	28.4	62.6	T11(M8)
EE-LPL2-600M	2	636	600	225	8.9	181	7.13	350	13.78	365	14.37	33.1	73.0	T11(M8)
EE-LPL2-800M	2	848	800	303	11.9	181	7.13	350	13.78	365	14.37	44.5	98.1	T11(M8)
EE-LPL2-1000M	2	1060	1000	370	14.6	181	7.13	350	13.78	365	14.37	55.8	123.0	T11(M8)