

# **Technical Specification**

# LB-400-500kW-COM Automatic Load Bank

#### 1 Foreword

This solution introduces LB-400-500kW-COM Automatic Load Bank and its accessories, including their function, performance, usage, structure, providing users with a high efficient and reliable choice to test generator.

All the pictures quoted in this agreement are for reference only.

### 2 Testing System

We do not supply testing cable, PC and printer if not specified.



# 3 Supply List

The following form presents the accessories provided when we make shipment.

Items	Quantity	Remark
LB-400V-500kW-COM Automatic Load Bank	1	
Power Cord	1	3 meters
RS485	1	10 meters
RS485/RS232/USB Converter	1	
Documents accompanied with shipment	Quantity	Remark
Manual	1	
Packing List	1	
Data Managing Software	1	



# **4 Technical Parameter**

Technical Parameter		
Rated Voltage & Frequency	<b>400VAC</b> ; 3 phase 4 wire, 50Hz	
Max Load Power	510kW at 400V	
Load Steps	Resistive Load: 1, 2, 2, 5, 10, 20, 20, 50, 100, 100, 200kW	
Power Factor	1	
Load Tolerance (each step)	±5%	
Load Tolerance (overall)	±3%	
Display Meter	Multiple function meter	
Fan Control Power	Auxiliary/external power single phase 110V 120V 130V 200V 210V 220V 230V 240V 50/60Hz	
Wire Connection	Load bank input——busbar Control power input——3-core socket	
Communication Interface	RS485	
Insulation	F	
Way of Working	Continuous Working	
Cooling	Forced air, horizontal air intake and exhaust cooling	
Transportation	With lifting eyes and wheel castors	
Color	As request	
Dimensions	993*1074*1227mm Width*Length*Height	
Weight	400kgs	
	Operating Environment Parameter	
Ambient Temperature	-20°C∼+50°C	
Using Place	Indoor	
Altitude	≤ 2500 meters	
Relative Humidity	≤ 95%	
Atmospheric Pressure	86∼106kPa	
Brands of Main Components		
Contactor	Schneider	
Fuse	MIRO	
PLC	Siemens	



#### **5 Functions**

- 1) 3- line LED multi-function meter can display real-time voltage and current of three phase and each phase, resistive power, power factor, apparent power, frequency and running time of generator set.
- 2) User can pre-set the power then press the master load button.
- 3) Control mode: user can choose local control or intelligent control (through PC with our data management software).
- 4) Control mode interlock: there is switch in control panel to choose control mode, other control mode is invalid if user choose one control mode.

#### **6 Protection**

- 1) Have emergency stop button.
- In case of over-load, over-heat, short circuit, load bank will automatically remove load and give alarm.
- 3) Fan protection: Load bank could not load before power of fan is on.
- 4) Give alarm when any fan is abnormal or with insufficient air volume.
- 5) Protection button: there are some protection buttons can be switched off when false alarm or for special requirements.


# 7 Data Processing Software

- 1) Automatic load: User can set several periods of power and duration and in turn of  $0\% \rightarrow 25\% \rightarrow 50\% \rightarrow 75\% \rightarrow 100\%$  or 110% then  $\rightarrow 75\% \rightarrow 50\% \rightarrow 25\% \rightarrow 0\%$ .etc to make automatic load testing.
- 2) Can make parallel testing for several units.
- 3) Data can be saved, could display real-time data and history data.
- 4) Charts and graphs can be exported in format of JPG while testing data exported in Excel and Word format, and all can be printed.












# **8 Pictures**









Control panel

# 9 After-sale Service

- (1). Warranty period is one year.
- (2). If required, technicians will be sent to help customer install, debug or repair the machine by the user's cost.
- (3). Customer has the right of technical consulting service for free forever.